



(12) **United States Patent**  
**Ben Nun**

(10) **Patent No.:** **US 8,956,409 B2**  
(45) **Date of Patent:** **\*Feb. 17, 2015**

(54) **ACCOMMODATING INTRAOCULAR LENS  
ASSEMBLIES AND ACCOMMODATION  
MEASUREMENT IMPLANT**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(75) Inventor: **Joshua Ben Nun**, D.N. Vitkin (IL)

3,950,082 A 4/1976 Volk  
4,122,556 A 10/1978 Poler

(73) Assignee: **Nulens Ltd.**, Herzliya Pituah (IL)

(Continued)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 685 days.

FOREIGN PATENT DOCUMENTS

This patent is subject to a terminal disclaimer.

EP 0 156 472 A 10/1985  
EP 0637503 B1 10/1998

(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **12/906,598**

Chu, Ralph Y. and Buliano, Megan, Accommodating IOLS by Ralph Chu et al, Cataract & Refractive Surgery Today, May 2004.

(22) Filed: **Oct. 18, 2010**

(Continued)

(65) **Prior Publication Data**

US 2011/0035002 A1 Feb. 10, 2011

*Primary Examiner* — Corrine M McDermott

*Assistant Examiner* — Joshua Levine

(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP

**Related U.S. Application Data**

(63) Continuation of application No. 11/568,416, filed as application No. PCT/IL2005/000456 on May 1, 2005, now Pat. No. 7,842,087.

(60) Provisional application No. 60/589,567, filed on Jul. 21, 2004.

(30) **Foreign Application Priority Data**

Apr. 29, 2004 (IL) ..... 161706

(51) **Int. Cl.**  
**A61F 2/16** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **A61F 2/1616** (2013.01); **A61F 2/1648** (2013.01); **A61F 2/1613** (2013.01); **A61F 2/1635** (2013.01)

USPC ..... **623/6.37**

(58) **Field of Classification Search**

USPC ..... 623/6.37–6.41

See application file for complete search history.

(57) **ABSTRACT**

A haptics system for retaining an accommodating intraocular lens (AIOL) in a human eye has an anterior surface and a posterior surface, and at least one shape memory optical element resiliently elastically deformable between a natural shape with a first Diopter strength and a deformed shape with a second Diopter strength different than the first Diopter strength whereby the AIOL has a continuously variable Diopter strength between a minimum Diopter strength for distance vision purposes and a maximum Diopter strength for near vision purposes. The haptics system includes a main body with a longitudinal axis intended to be co-directional with the human eye's visual axis and at least two haptics tangentially extending from said main body in opposite directions in a plane perpendicular to the haptics system's longitudinal axis, and each with at least one pointed puncturing member for penetrating the tough connective tissue of the human eye's sclera for self-anchoring implantation in the human eye's annular ciliary sulcus at at least two spaced apart stationary anchor points for retaining the AIOL along the human eye's visual axis.

**6 Claims, 7 Drawing Sheets**

